

DATASHEET

19" Wall Housing IP55, 16U, Steel Door, Depth 600 mm,
RAL7035



General data

Steel sheet housing with welded corpus, completely pre-assembled

Right- and left-sided metal covered air inlets for passive ventilation

Side walls not detachable

Roof hinged, inner roof prepared for mounting of Plug&Play fan unit Art.-No. 691656GR (cable not included, please order separately, e.g. Art.-No. EK504.x)

Bottom with PG glands 1 x PG48, 2 x PG21 and 3 x Ø 20 mm PVC blind grommets

For depth 450 mm inside 2 x 19" profile rails front-sided, galvanised, with numbering of rack units (U)

For depth 600 mm inside 4 x 19" profile rails (2 front, 2 rear), galvanised, with numbering of rack units (U)

Front door steel sheet with reinforcement and 3-point bar locking, lockable, with profile half-cylinder acc. to DIN 18252 / EN1303

Profile half-cylinder exchangeable by customer

Cabinet parts inside completely earthed

Max. load 100 kg

Paint finish RAL7035, light grey

Protection degree IP55

Plinth for use as standing cabinet available as option

Included accessories: 4 x Wall mount angle, 2 x key

Allgemeine Daten	
Modular spacing	482.6 mm (19 inch)
With front door	True
Surface finishing	powder coating
With roof plate	True
With sidewall	True
Mounting level	Front and rear
Model	With permanent frame
With earthing	True
Type of profile rail	L-shaped

General data	
Type of ventilation	Passive
Demountable	True
Number of cartons	1
Degree of protection	IP55
Number of doors	1
Material	steel